



WASHING

FWS-30 TP2 NORMAL SPIN WASHERS



Fagor commercial FWS washers are solid-mount and perfect for laundromats, hotels, hospitals, nursing homes, and more.

You'll see a reduction in water and energy consumption, better wash results, and longer garment/linen life.

TOUCH PLUS CONTROL

- 7" touchscreen, intuitive and flexible programming
- USB Connection: software free of charge
- 37 languages, continually expanded
- Upload videos to display, use for ads, instructions, etc.

G-FORCE EXTRACTION

- 25-100 lb capacity washers: 200G
- 135-180 lb capacity washers: 150G
- Fully programmable

CONNECTIVITY

- FagorKonnnect - IoT
- Provided at NO extra charge
- Manage your laundry anywhere, at anytime, 24/7
- Create programs, special promotions, access real-time reports, have service alerts go directly to technicians, and much more.

EFFICIENCY

- Low energy and water consumption

VERSATILITY

- Easily converts from OPL to COIN
- Electric or steam
- Wetcleaning ready, programmable
- Extraction speed and water levels easily programmed for applications such as wetcleaning, firehouse, etc.

ERGONOMICS

- Reversible doors, standard
- Industry leading large doors, for easy loading and unloading

MAINTENANCE

- Hinged front control panel, easy and ergonomic access
- Technical menu, statistics for technicians
- Common parts across all models

MORE INFO

- Hard mount washer
- Stainless steel front and top panels
- Anchor to floor with anchoring base
- 3 water inlets
- CE, WRAS approved

OPTIONS

- FagorKonnnect at no extra charge
- Auto unlock kit for door (in case of power failure) - recommended for vended laundries
- Silicon gasket
- 6 extra dosing signals
- Normally closed drain valve
- Double drain kit
- Anchoring base
- Ready for EcoTank
- Sluice - Drum
- Tropicalized model: protected board (TOUCH II)
- Coin/token kit

DRUM		FWS - 30 TP2	
Load capacity 1:9 / 1:10	Lb.	30.9/28.7	
Volume	CU.FT	4.6	
Diameter	In	24.4	
Depth	In	16.9	
GENERAL			
Washing speed / Spinning speed	r.p.m.	53/759	
G Force	G-Force	200	
Maximum force transmitted	KN	2.31 ±4	
Frequency-dynamic force	Hz	8,93	
Noise level	dB	<70	
Vend / OPL		Yes / Yes	
Double drain		Opt.	
SLUICE option		Yes	
DOOR			
Height center door / Height door	In	22.5/12.2	
Diameter	In	14.7	
POWER			
Motor	Hp	1.5	
Electric heating power	kW	9	
Total electric power (electric model)	kW	9.5	
Total electric power (hw, steam model)	kW	1.1	
CONNECTIONS			
Voltage 208-240/60/1~ + G	N° x AWG / A	3 x 6 / 50A	3x 14 / 15A
Voltage 208-240/60/3~ + G	N° x AWG / A	4 x 10 / 32A	-
Voltage 440-480/3 ~ + G	N° x AWG / A	4 x 12 / 20A	
Steam inlet (Steam model)	inch	1/2"	
Water inlet	inch	3/4"	
Water main pressure	Kg/cm2	2-4	
Maximum water consumption	Gal/h	20,8*	
Drain	inch	3"	
Drainage capacity	Gal/min	52.8	
DIMENSIONS			
Net Width / Gross Width	In	28.31/30.8	
Net Depth / Gross Depth	In	32.68/39.0	
Net Height / Gross Height	In	45.59/55.2	
Net weight / Gross weight	Lbs.	526/540.2	

* Programmed No. 20, 75% load

